

MX SERIES

Angled Blending Reel TMR Mixer
stationary or mobile



- A unique Rovibec Agrisolutions design, this angled blending reel mixer is the answer for the producer in search of a really superior quality mixer suitable for use with a medium to large size herd.
- This blade mixer will allow you to prepare recipes of exceptional quality for your animals thanks to its smooth operation and the positioning of its robust angular blades which blend all the ingredients of your recipe into a perfectly homogeneous mixture without damaging or tearing the fibres so important for healthy nourishing of your herd.
- Either combined with a PF 600 hay processor or a PF 500 hay chopper, you will be able, in a single operation, to cut your dry or moist hay to your desired length and combine it directly with your recipe while it is blending thus eliminating virtually all dust as the hay is sent directly into the mixer from the bottom where it is immediately incorporated into your mixture while the blades continue to gently blend the mixture.



Mélangeur à pales angulaires jumelé à un PF500



The RTM mixer with angular blades is built to order according to the needs of the individual dairy producer. Certain features are offered as options. Features, specifications and dimensions are subject to change without notice.



The very large top opening is an important advantage for loading material and delivery by augers or conveyors.

The optional high resistance coating on the interior of the Tub reduces wear due to friction as well as the corrosive action of silage. The robust angular blades gently displace material in all directions ensuring complete mixture and perfect homogeneity without damaging the fibres.

On closer examination of Rovibec Agrisolutions' angled blending reel mixer, you will note its incomparable mechanical design, unique of its kind and a veritable model of simplicity which greatly facilitates maintenance. Furthermore, its robust construction is your guarantee of a



long service life.



Specifications

MODEL RTM	MOTOR HP	LENGTH In / mm	WIDTH In / mm	HEIGHT In / mm	TOTAL CAPACITY ft ³ / m ³	MIXTURE CAPACITY ft ³ / m ³	WEIGHT lbs/kg
MX 660	5	94 / 2390	92 / 2340	87 / 2210	170 / 4,2	150 / 4,2	3377 / 1535
MX 860	7.5	112 / 2840	92 / 2340	87 / 2210	265 / 7,5	200 / 5,7	4620 / 2100
MX 1060	7.5	135 / 3430	92 / 2340	87 / 2210	332 / 9,4	270 / 7,6	6050 / 2750
MX 1260	10	156 / 3960	92 / 2340	87 / 2210	398 / 11,7	324 / 9,2	7315 / 3325
MX 1460	10	187 / 4750	92 / 2340	87 / 2210	465 / 13,2	378 / 10,7	8580 / 3900
MX 880	7.5	112 / 2840	110 / 2790	100 / 2540	355 / 10,1	300 / 8,5	5225 / 2375
MX 1080	7.5	135 / 3430	110 / 2790	100 / 2540	442 / 12,5	385 / 10,9	6600 / 3000
MX 1280	10	157 / 3990	110 / 2790	100 / 2540	530 / 15,1	450 / 12,8	7700 / 3500
MX 1480	10	187 / 4750	110 / 2790	100 / 2540	618 / 17,5	525 / 14,9	8855 / 4025
MX 1680	10	213 / 5410	110 / 2790	100 / 2540	707 / 20	600 / 17	10230 / 4650
MX 1880	10	231 / 5870	110 / 2790	100 / 2540	795 / 22,5	675 / 19,1	11495 / 5225



